

Zephyr Measurement Certificate

Mackay GRP Hull

Owner's Name;	
Owner's Address;	
Email Address;	
Hull No;	Boat Name;
Measurer;	Measurement Date;

HULL MEASUREMENTS	Min	Max	Actual	Comment
Hull overall length, beam and beadings. Mast collar diameter, position and height. Chainplate location. Coamings. Mast step height. Centrecase location and depth.				ZOA approved
Rudder gudgeon pivot		100		
Hull weight – excluding correctors	58			
Corrector weights if fitted – 2 required	Weight each: -			
MAST MEASUREMENTS				
Length – base to halyard bearing surface		5640		
Forestay intersection to halyard bearing surface	1525	1830		
Sidestay intersection to halyard bearing surface	1525	1830		
Gooseneck pivot point from mast		35		
BOOM MEASUREMENTS				
Track cutaway from mast extrusion		260		
CENTREBOARD MEASUREMENTS				
Length beneath stoppers		1370		
Width		292		
Thickness		22		
RUDDER MEASUREMENT				
Thickness		22		
SAIL				
Doyle with logo and hull numbers attached			Y / N	
YNZ SAFETY REQUIREMENTS				
Towing eye			Y / N	
Rudder assembly secured to hull			Y / N	
Centreboard securing lanyard			Y / N	
Bailer			Y / N	
HULL IDENTIFICATION NUMBER				
Keelson, starboard side of c/case or transom			Y / N	
Both sides of hull min 50mm high			Y / N	

NOTES